

Power

AlphaGen™ Portable

3.0kW Portable 36/48Vdc Generator System for Emergency Backup



- DC technology requires no Automatic Transfer Switch (ATS)
- No need to disconnect or reconnect power supply to utility power
- Selectable output for 36 or 48Vdc operation up to 3000W
- Super quiet operation only 65dBa @ 7m/22ft
- Completely enclosed, water resistant for safe operation in the field
- Oversized metal gas tank with level gauge for extended runtimes of up to 20hrs

Alpha expands its generator family to include a portable 3.0kW DC generator. The compact, lightweight AlphaGen generator is designed specifically for powering cable television, telecommunications and broadband applications that do not have integrated generators as a primary component of the power system.

The portable generator incorporates several technological advantages including: 36 or 48V selectable dual voltage output based on Permanent Magnet Generator (PMG) technology, 3000W of power and oversized fuel tank for up to 20hrs of runtime at 25% load or 7.2hrs at 100% load.

Additional features include a convenient front panel with a keyed on/off switch, output connector, output indicators, voltmeter, fuel valve and engine choke.



AlphaGen Portable 3.0kW Series

Specifications

Part Number: 041-028-10
 Engine: Honda GX 200 6.5hp, Air-cooled, OHV, Single cylinder, Manual recoil starting, Manual choke
 Rated Power: 2800W continuous, 3000W max.
 Alternator: Permanent Magnet, brushless, bearingless

Dual range selector

36V: 39.5Vdc nominal at generator output connector
 48V: 52.5Vdc nominal at generator output connector
 Output Regulation: 1Vdc
 Control Features: Automatic Voltage Regulation
 Electronic Governor
 Over current Protection
 Analog voltmeter with back light

Cable Interface: Anderson type SBE-80 connector
 Fuel Tank: 3.4 gallon metal tank with level gauge

Runtime

@ 25% Load: 20hrs
 @ 80% Load: 10hrs
 @ 100% Load: 7.2hrs
 Audible Noise: Approx. 65dBa @ 7m under full load
 Frame: Fully Enclosed
 Dry Weight: Less than 118lbs (53.5kg)
 Dimensions (in): 22H x 17.6W x 25.9D
 (mm): 569H x 480W x 655D
 Agency: CSA C22.2 No. 100-95, 107.1-01,
 107.2-M89, 0.4
 FCC part 15B Class A

Required Accessories

Output Interface Cable: Available in 10', 30' or 50' lengths
 Battery Interface Cable: Choose Ring Lug, Heavy-Duty Alligator Clamp, or Y-adaptor*

* Connects the power supply's battery input directly to the generator



Output Interface
 10' P/N 875-324-22
 30' P/N 875-324-20
 50' P/N 875-324-21



Ring Lug Battery Interface
 P/N 874-946-21



Alligator Clamp Battery Interface
 P/N 874-946-20



Y-Adaptor Battery
 P/N 874-946-22


Optional Accessories

DCX-PG-WK: Portable generator wheel kit (P/N 745-793-20)
 DCX-PG-HANDLE: Locking handle (P/N 745-792-20)
 AG-PG-TOOL: Punch tool kit for enclosures (P/N 745-131-20)
 AG-PG-UK: Enclosure upgrade kit (P/N 745-131-21)
 AG-CAB-KIT: Cable bag with cable and key lanyard (P/N 745-764-21-001)


3.0kW Portable Generator Sound Levels

Ambient background noise level at 45dBa
 All readings are 8 point averages

Generator at 100% rated load



Generator at 25% rated load (typical)



AlphaGen front view



AlphaGen with optional Wheel Kit with Locking Handle and optional canvas cable bag



AlphaGen Portable Trailer

For contact information visit www.alpha.com

The Alpha Group >

North America	Europe, Middle East & Africa		Asia Pacific	Latin & South America
USA Tel: +1 360 647 2360 Fax: +1 360 671 4936	Cyprus Tel: +357 25 375 675 Fax: +357 52 359 595	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21	Lithuania Tel: +370 5 210 5291 Fax: +370 5 210 5292	P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988
Canada Tel: +1 604 436 5900 Fax: +1 604 436 1233	Russia Tel: +7 495 925 9844 Fax: +7 495 916 1349	United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870		Contact USA office