

# SX 48RU Rack

## 19" and 23" Rack Enclosure

- Tool free installation and removal of roof
- Rapid adjustment of leveling feet
- Tool free PDU mounting provisions
- Numbered RU positions
- Light-weight, half-height side panels
- Tool free cable management options
- 48RU models roll through 2 meter doorways
- Cable openings for overhead or underfloor applications



AR3107



AR3157

### SX 48RU Rack

AR3107	
Weight (lb/kg):	304.1 / 138.23
Dimensions (in/mm):	42.13 x 23.62 x 88.9 / 1070 x 600 x 2258
Weight Capacity - Static Load (lb/kg):	3000 / 1363.6
Weight Capacity - Dynamic Load (lb/kg):	2250 / 1022.7



### SX 48RU Rack

AR3157	
Net Weight (lb/kg):	372 / 169.09
Dimensions (in/mm):	42.13 x 29.53 x 88.9 / 1070 x 750 x 2258
Weight Capacity - Static Load (lb/kg):	3000 / 1363.6
Weight Capacity - Dynamic Load (lb/kg):	2250 / 1022.7



Enclosures providing cooling, power distribution, cable management and environmental monitoring for applications in IT environments. NetShelter® SX is the next generation rack enclosure solution influenced by 10 years of customer feedback addressing current IT market trends for high-density server and networking applications. The NetShelter SX provides a reliable rackmounting environment for mission-critical equipment.