

# Power

## Tempest Te17

Outdoor Enclosure



Tempest Te17  
(shown with 5000BTU air conditioner,  
bottom compartment, and solar shield)

- Designed for outdoor network applications
- Easily transportable
- Durable welded aluminum construction
- Variety of configurations possible with 23RU of space
- Compact footprint
- Competitive pricing

**Tempest brings convenience and versatility to outdoor power system enclosures.** In addition to ADSL, TI, and fiber optic transmission system (FOTS) facility applications, the Te17 is designed to meet the requirements of WiMax service providers.

Engineered to fit through commercial doorways and stairwells, installation and maintenance are easy to conduct even on remote rooftop sites. Welded aluminum construction provides structural integrity that will withstand seismic events and harsh weather conditions. The Te17 is designed with the flexibility to house equipment from various vendors and to expand as powering needs change.

Trust Tempest outdoor enclosures to provide the ultimate protection for network equipment.

## Tempest Te17 Outdoor Enclosure

### Electrical

Consult factory for AC load center options for specific equipment requirements

### Mechanical

#### Main Compartment

Dimensions  
mm: 1092H x 762W x 711D  
inches: 43H x 30W x 28D

#### Bottom Compartment

Dimensions  
mm: 356H x 762W x 711D  
inches: 14H x 30W x 28D

#### Solar Shield

Dimensions  
mm: 25H x 762W x 711D  
inches: 1H x 30W x 28D

#### Enclosure Assembly

Dimensions  
mm: 1473H x 762W x 711D  
inches: 58H x 30W x 28D

**Rack Units:** 23" rack 23RU

**Weight:** 204kg (450lb) approx without customer equipment

### Other Info.

**Alarm**  
Connection: Terminal block  
Description: High/low temperature  
Intrusion

**Chassis Ground:** Multiple connection  
Buss bar located in cabinet

**Security:** Padlockable doors with socket pin-head key

### Standards

CSA: C22.2 No 60950-01-03  
UL: Std. No 60950-01  
CABINET: NEMA Type 3R (CSA C22.2 No 94-M91)  
SEISMIC: Designed to Zone 4 requirements

### Related Components

**Heating & Cooling:** Contact factory on HVAC options for specific environmental conditions



Tempest Te17  
(shown configured to customer specification)

For contact information visit [www.argusdcpower.com](http://www.argusdcpower.com)

The Alpha Group >	Europe, Middle East & Africa	Asia Pacific	North America	Latin & South America	
	<p><b>Cyprus</b> Tel: +357 25 375 675 Fax: +357 25 359 595</p> <p><b>Germany</b> Tel: +49 9122 79889 0 Fax: +49 9122 79889 21</p> <p><b>South Africa</b> Tel: +27 11 608 1936 Fax: +27 11 608 1948</p>	<p><b>Russia</b> Tel: +7 495 916 1854 Fax: +7 495 916 1349</p> <p><b>United Kingdom</b> Tel: +44 1279 501110 Fax: +44 1279 659870</p>	<p><b>P.R. China</b> Tel: +86 769 533 2600 Fax: +86 769 532 6603</p>	<p><b>Canada</b> Tel: +1 604 436 5900 Fax: +1 604 436 1233</p> <p><b>USA</b> Tel: +1 360 671 7054 Fax: +1 360 671 7096</p>	<p><b>Mexico</b> Tel: +52 55 5280 6990 Fax: +52 55 5280 6585</p>